

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE


Latitudes Series LED Lighting

2' x 2' Surface Mounted White Panel for Harsh Environments

Ligature & Vandal Resistant • IK10 Impact Resistant • 90 CRI

Up to 60,000 Hour Rated Life (L70) • Wet Location (Covered Ceilings)

LSS-22VFP



Specifications

Delivered System Performance

- Nominal Lumens: **MUST SPECIFY**
- 2500L**
- 1500L**
- Select trim & beam distribution: WFL
- Select color (CCT): see chart; 80+ CRI standard; Option -HC for 90+ (15% lumen loss)
- 60,000 Hour Rated Life (L70)

Thermal Management

- Heavy gauge aluminum construction provides maximum heat dissipation for cool LED operation. Extends life of all components

LED Driver - INTERNAL

- Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F)
- 0-10V CCR 10% dimming standard
- 120-277V / 50-60 Hz standard; load insensitive
- Enclosed in aluminum housing

IK10 Vandal Resistant Design

- Rigid, tempered heavy gauge 6063-T5 aluminum housing and single-piece frame with seam welded corners and keys
- Rustproof and corrosion resistant: Exceeds 1000 hour ASTM 5% salt spray test
- Flush center pin tamperproof screws
- Tamperproof tool included
- High strength clear flat polycarbonate (0.220") - environmental side
- Extruded acrylic wave guide provides unparalleled uniformity
- Lightweight: minimizes ceiling load

Outlet Box

- UL listed J-box; prewired 16 GA steel with ½" knockouts

Installation

- Direct mount to any hard surface ceiling; mounting hardware by others
- Suitable for indoor use

UL, C-UL (Canada) Listings

- Wet, damp or dry locations, covered ceilings

FCC Compliance

- FCC Part 15 certified for EMI/RFI emissions

FIVE YEAR Limited Warranty

- Complete standard fixture

Made in the USA BABAA Compliant	Vandal Resistant	IK10 Impact Resistant	Natorium See Option -NAT	BioGard™ See Option -BG	FCC Part 15 Certified	UL Listed Wet, Damp, Dry
------------------------------------	------------------	-----------------------	-----------------------------	----------------------------	-----------------------	-----------------------------



Options and Ordering Configuration

(Example: LSS-22VFP-2500L-41K-D1-NAT)

Must Specify			Optional		
Model	Lumens	CCT & CRI	Driver Options	Housing/Trim Options	Other Options
LSS-22VFP	-1500L -2500L	-35K: 3500K -41K: 4000K	(Blank): Standard 0-10V CCR 10% dim -D1: 0-10V 1.0% dim -D6: Triac 100-10% dim	(Blank): Standard white enamel -35: Silver enamel -37: Dark bronze enamel -38: Black enamel -BG: BioGard™ anti-microbial white -BKBG: BioGard™ anti-microbial black -94: Custom color; consult factory -94BG: BioGard™ anti-microbial custom color finish	(Blank): None -99: Special modification; consult factory -NAT: Modified for natorium use


THIS FIXTURE HAS BEEN DISCONTINUED. CONTACT FACTORY FOR ALTERNATIVES.

Dimensions



Photometry - Installed Complete Fixture

LM-79 IESNA Certified Photometry from Independent Lab



THIS FIXTURE HAS BEEN DISCONTINUED. CONTACT FACTORY FOR ALTERNATIVES.

LED manufacturers maintain a tolerance of +/-7% on flux (lumens) and power (electrical) measurements.

LIMITED WARRANTY: CATALOGED KIRLIN FIXTURES ARE WARRANTED FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL FOR FIVE YEARS FROM DATE OF PURCHASE. INSTALLATION, USE, MANUFACTURE, AT THE OPTION WILL REPLACE OR REPAIR SUCH FIXTURE OR RETURN THE PURCHASE PRICE ON PRESENTATION OF PROOF OF PURCHASE AND DEFECTIVE FAILURE AT THE OFFICE OF MANUFACTURER WITHIN THE YEARS OF ORIGINAL SHIPMENT. LIABILITY OF MANUFACTURER IS LIMITED TO THE FOREGOING AND MANUFACTURER SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES, DIRECT OR INDIRECT, SUSTAINED OR SUFFERED BY PURCHASER OR ANY PERSON. THIS WARRANTY IS APPLIED TO THE BUYER IN PLACE OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. SELLER DOES NOT WARRANT AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, NOR WILL ANY ORAL STATEMENT CONSTITUTE A WARRANTY OR AMEND THIS SPECIFIC WARRANTY. ABNORMAL USE, ABUSE OF THE FIXTURE, IMPROPER INSTALLATION, OR REPAIR OR MODIFICATION OF THE FIXTURE WITHOUT PRIOR WRITTEN AUTHORIZATION FROM THE MANUFACTURER WILL RENDER THE WARRANTY VOID.