

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

# Lighting for Patient Spaces

## Strait Secure Static and Tunable White Slot

2.5" Recessed • Ligature Resistant • IK10-Rated

Delivers Up To 1200 Lumens Per Foot • LM-80 Qualified • LM-79 Certified

## Specifications

### Luminaire Features

- Vandal- and ligature-resistant linear slot light
- Shallow extruded aluminum housing with vandal- and ligature-resistant frame
- For use in behavioral health, transportation, education, and anywhere else a secure fixture is needed
- White finish standard, or see options below
- Color temperature: see chart below; CRI: 90+

### LED Driver - INTERNAL

- Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F)
- 0-10V 1.0% dimming standard
- 120-277 volt

### Vandal-Resistant Trim/Lens Assembly

- Ligature resistant smooth single-piece aluminum frame with 0.22" polycarbonate lens

- Discreet tamperproof screws placed along edge of frame to fixture housing
- Tamperproof tools included: one hex key per 10 fixtures and one FlexDrive bit per order for easy installation; additional FlexDrives can be purchased separately
- Anti-pixelation optical film included above polycarbonate lens


### Scenic Panel Image (Optional)

- Acrylic scenic panel (Over 100 selections from Kirlin or customer-provided) above polycarbonate
- Visualize your design with Kirlin's [Scenic Configurator](#) tool

### Installation

- Securely mounts to hard ceiling for use in behavioral health environments

## VRL-02SWM



- Mount with #6 sheet rock fasteners, supplied by others
- Indoor/outdoor in ceilings up to 1 1/8" thick
- Minimum spacing between fixtures (frame edge to frame edge) is 2.5" when using the hex key and 4.5" when using the FlexDrive
- Minimum spacing between fixture and a wall is 2.5" when using the hex key and 6.0" when using the FlexDrive

### UL, C-UL (Canada) Listings

- Damp or dry locations, covered ceilings
- Type IC; approved for direct contact with insulation

### FIVE YEAR Limited Warranty

- Complete standard fixture

**Declare.**



Made in the USA



Tunable White



IK10 Impact Resistant



Vandal Resistant



BioGard™



Nataorium  
See Option -I66



IP66  
See Option -I66




UL Listed  
Damp, Dry

## Options and Ordering Configuration

(Example: VRL-02SWM-4FT-1000L-DD-6527-TW-BG)

Must Specify					Optional		
Model	Length	Lumens/FT	Beam	CCT & CRI	Dimming	Trim Options	Other Options
VRL-02SWM							
	-2FT -4FT -6FT	-1200L -1000L -750L -500L -XXXXL*	-DD: Direct distribution -AS: Asymmetric -IMG: Image behind polycarbonate lensing; see <a href="#">Scenic Image Gallery</a> for image options or contact factory for custom image; Available with -0500L or -0750L only	-30K: 3000°K, 90+ CRI -35K: 3500°K, 90+ CRI -40K: 4000°K, 90+ CRI -6527: Tunable white; 6500°K - 2700°K, 80+ CRI; Available up to -0750L lumens/ft	(Blank): 0-10V dimming to 1% for static white -D2: 0-10V dimming to 0.1% for static white -D7: DALI dual drive 0.1% dimming driver instead -TW: Dual 0-10V Tunable White control with 0.1% dimming; Available with -6527 only -TW7: DALI dual drive 0.1% tunable white dimming driver instead; Available with -6527 only -TW8: DALI DT8 dual drive 0.1% tunable white dimming driver instead; Available with -6527 only	(Blank): IK10-rated white trim with polycarbonate lens  <b>Trim Finishes</b> -35T: Silver enamel -37T: Bronze enamel -38T: Black enamel -BG: BioGard anti-microbial white -BKBG: BioGard anti-microbial black -94: Custom color; see page 3 for recommended custom colors; consult factory -94BG: BioGard anti-microbial custom color finish  <b>Other Trim/Lens Features</b> -I66: IP66 rated trim and lens; Meets ASTM E283 restricted airflow of 2CFM; Nataorium rated	(Blank): None  -99: Special modification; consult factory

## Length of Housing



**Minimum spacing between fixture and a wall is 2.5" when using the hex key and 6.0" when using the FlexDrive**

Static White



NOMINAL LUMENS PER FOOT	LUMEN FACTOR	NOMINAL WATTS PER FOOT	LPW FACTOR
-1200L	1.00	16.2	1.00
-1000L	0.78	12.6	1.07
-750L	0.52	8.1	1.04
-500L	0.42	5.5	1.25

## Tunable White

NOMINAL LUMENS PER FOOT	LUMENS PER FOOT	NOMINAL WATTS PER FOOT	LPW FACTOR
<b>-750L-27K</b>	537.1	7.8	69.3
<b>-750L-65K</b>	583.9	7.7	75.8

## Photometry from L.L.I., Allentown, PA


LM-79 IESNA Certified Photometry from Independent Lab




## Recommended Custom Colors

The below colors match Kirlin's Scenic Patterns for a cohesive look throughout the space.  
To be used with option code -94.

### Calming Colors




Pale Marigold




Peaceful Pine



Moonlit Bay



Dreamy Dusk



Mudstone Magic




Soft Slate


### Vibrant Colors



Electric Ember



Hot Orchid



Lemon Zing




Kiwi Kick



Caribbean Lagoon



Cerulean Wave



Glam Grape

Due to variations in monitor settings and screen resolutions, the appearance of colors, textures, and details in the images may differ from the actual product.